

Application No. 10/650,038
Docket No. 0902-005
Response (03/23/06) to OA (9/23/05)

Amendments to the Claims:

This listing of claims will replace all prior versions, and listings, of claims in the application.

Listing of Claims:

1 - 7. (Canceled)

8. (Currently Amended) A microscopy system for visualizing a fluorescence of a fluorescent substance in an object to be inspected, wherein the microscopy system comprises:

- a microscopy optics having
 - a first beam path for optically imaging an object region onto a light detecting component of a first camera for generating first image data representing images of the object region with light including wavelengths of a first wavelength range comprising a fluorescent emission wavelength of the fluorescent substance, and
 - a second beam path for providing a magnified first representation of the object region, wherein the first representation represents images of the object regions with light including wavelengths of a second wavelength range comprising at least visible light;
- an image memory for storing a set of first image data representing plural images of the object region sequentially detected by the first camera during at least a time duration; and
- a display system ~~for configured to sequentially display~~ displaying a sequence of plural

Application No. 10/650,038
Docket No. 0902-005
Response (03/23/06) to OA (9/23/05)

second representations generated from at least a subset of the set of first image data, ~~wherein~~
such that the sequence of plural second representations ~~is~~ are displayed in superposition with the
first representation for observation by ~~the a~~ user.

9. (Currently Amended) The microscopy system according to claim 8, wherein the
display system is configured for repeatedly displaying the series of plural second representations
in superposition with the first representation.

10. (Currently Amended) The microscopy system according to claim 8, further
comprising a controller configured to select the subset of the set of first image data from the set
of first image data based on intensities of the plural images represented by the first image data ~~of~~
~~the first set.~~

11. (Original) The microscopy system according to claim 8, further comprising a
controller configured for selecting the subset from the set of first image data based on differences
of intensities of the images represented by the first image data of the first set.

12 - 29. (Canceled)

Application No. 10/650,038
Docket No. 0902-005
Response (03/23/06) to OA (9/23/05)

30. (Currently Amended) The microscopy system according to claim 8, wherein the ~~first~~ second beam path comprises at least one ocular for representing the ~~images~~ magnified first representation of the object region.

31. (Currently Amended) The microscopy system according to claim 30, wherein the display system is further configured to superimpose the plural second representations with the ~~first~~ second beam path directed to the ocular.

32. (Currently Amended) The microscopy system according to claim 8, wherein the first beam path comprises at least one light detecting component of a second camera for generating second image data representing images of the object region with visible light, and wherein the display system is further configured to display a representation of the second image data ~~the second representation is displayed by the display system~~.

33, 34. Canceled

35. (Currently Amended) A microscopy method of visualizing a fluorescence of an object to be inspected, the method comprising:

displaying a magnified first representation of the object for observation by a user,
wherein the fluorescence of the object is substantially not visible in the first representation;
recording a series of fluorescent light images of the object during a time duration; and

Application No. 10/650,038
Docket No. 0902-005
Response (03/23/06) to OA (9/23/05)

displaying the recorded series of plural fluorescent light images of the object after the time period has lapsed such that the series of plural fluorescent light images is visible for the user and superimposed with the magnified first representation of the object.

36 - 39. Canceled

40. (Currently Amended) A method of treating an aneurysm of a patient, the method comprising:

clipping an aneurysm sac of the aneurysm using a clip;

injecting indocyanine green into the patient;

generating at least one fluorescence image of at least one artery adjacent to the clipped aneurysm; ~~and~~

assessing vascular blood flow of the at least one artery based on the at least one fluorescence image; and

assessing a complete blocking of the aneurysm sac with the clip based on the at least one fluorescence image.

41. (Withdrawn) The method of claim 35, further comprising:

illuminating the object with light including wavelengths higher than a predetermined

Application No. 10/650,038
Docket No. 0902-005
Response (03/23/06) to OA (9/23/05)

wavelength while recording the series of fluorescent light images; and

terminating the illuminating of the object with the light of the wavelengths higher than the predetermined wavelength, based on an analysis of the recorded fluorescent light images, and illuminating the object with light only including wavelengths smaller than the predetermined wavelength.

42. (Withdrawn) The microscopy method of claim 41, wherein a fluorescent substance is applied to the object when the object is illuminated with the light of the wavelengths higher than the predetermined wavelength.

43. (Previously Presented) The microscopy system of claim 8, wherein the fluorescent substance comprises indocyanine green.

44. (Withdrawn) The microscopy system of claim 8, further comprising:
an illumination system for providing at least one illuminating light beam directed onto the object region, wherein the at least one illuminating light beam includes light with wavelengths of the second wavelength range and an excitation wavelength of the fluorescent substance.

Application No. 10/650,038
Docket No. 0902-005
Response (03/23/06) to OA (9/23/05)

45. (Withdrawn) The microscopy system according to claim 8, wherein the light of the at least one illuminating light beam is emitted from one single light source.

46. (Withdrawn) The microscopy system according to claim 45, wherein the light source comprises one of a xenon lamp and a halogen lamp.

47. (Withdrawn) The microscopy system according to claim 8, wherein the illuminating system comprises a first filter disposed in a beam path of the illuminating system, wherein the first filter substantially eliminates light with a fluorescent emission wavelength of indocyanine green from the illuminating light beam.

48. (Withdrawn) The microscopy system according to claim 8, wherein the illumination system comprises a second filter disposable in a beam path of the illuminating system, wherein the second filter substantially eliminates light from the illuminating light beam having a wavelength higher than 710 nm.

49. (Withdrawn) The microscopy system according to claim 8, wherein the illumination system comprises a second filter disposable in a beam path of the illuminating system, wherein the second filter substantially eliminates light from the illuminating light beam having a wavelength higher than 690 nm.

Application No. 10/650,038
Docket No. 0902-005
Response (03/23/06) to OA (9/23/05)

50. (Withdrawn) The microscopy system according to claim 49, wherein at least one of the first and second filters comprises a transmissive filter or a reflective filter.

51. (Withdrawn - Currently Amended) The microscopy system according to claim 8, wherein

the illumination system comprises

a first filter which is positionable at a first position in which the first filter is disposed within a beam path of the illumination system, wherein the first filter eliminates light with wavelengths higher than a predetermined wavelength from the illuminating light beam, and ~~wherein the illuminating system comprises~~

an actuator for displacing the first filter from a second position in which the first filter is not positioned within the beam path to the first position; and

a controller configured for controlling the actuator for displacing the first filter from its second position to its first position based on an analysis of intensities of images represented by the set of first image data.

52. (Withdrawn) The microscopy system according to claim 51, wherein the predetermined wavelength is in a range of one of 690 nm to 720 nm, 720 nm to 750 nm, 750 nm to 780 nm, and 780 nm to 800 nm.